


## **UHZ** Type

## Flat Seat Insert Disk Holder





- Flat seat provides improved rupture disk sealing
- Available in nominal sizes ranging from 1/2" thru 30" in standard flange classes
- Standard materials of construction are: 316SS and carbon steel. Other materials available on request
- Permanently attached stainless steel nameplates are standard. Nameplates indicate flow direction and provide visual verification that holder assembly is properly oriented in the piping system
- Stainless steel safety designed side clips are standard, allowing for pre-assembly of disk into holder
- Fits type SFAZ, FDZ and FPBZ Series Disks
- Available options include: gauge tap; nipple and tee; excess flow valve; pressure gauge; J-hook; special facings and coatings



**PRESSURE** 

## **UHZ Holder Dimensions**

Nominal Size	ANSI Class	Height inches	O.D. inches	Estimated Weight Ibs.
1"	150	1.625	2.50	1.8
	300/600		2.75	2.3
1-1/2"	150	1.625	3.25	2.9
	300/600		3.63	3.9
2"	150	1.625	4.00	4.0
	300/600		4.25	4.8
3"	150	1.625	5.25	6.3
	300/600		5.75	8.5
4"	150	1.875	6.75	11.9
	300		7.00	13.5
	600		7.50	17.0
6"	150	2.500	8.63	20.2
	300		9.75	33.2
	600		10.38	41.1
8"	150	2.875	10.88	33.2
	300		12.00	51.8
	600		12.50	60.7
10"	150	3.250	13.25	53.3
	300		14.13	72.9
	600		15.63	135.7
12"	150	3.625	16.00	90.9
	300		16.50	105.7
	600		17.88	148.7

Contact ZOOK for alternate sizes and/or flange classes.

Bulletin no. 321101 Rev. 3 © 2000, 2001, 2013 ZOOK Enterprises, LLC, all rights reserved Printed in U.S.A. 12-13-1500-12M-CGG



**ZOOK Enterprises, LLC** 16809 Park Circle Drive Chagrin Falls, OH 44022 U.S.A.

Toll Free 800.543.1043
Phone 440.543.1010
Fax 440.543.4930
E-mail sales@zook.cc

**ZOOK Canada, Inc.** 4400 South Service Road Burlington, ON Can. L7L 5R8

Toll Free 800.370.6057
Phone 905.681.2885
Fax 905.681.8838
E-mail sales.canada@zook.cc

**ZOOK Europe, LTD.** 

Navigation House, Bridge Street Killamarsh, Sheffield UK. S21 1AL

Phone **0044 (0) 1909 560999**Fax **0044 (0) 1909 560860**E-mail **zookeurope@zook.cc**