

...provide over-pressure protection in sanitary piping system


SD Disks are an extension of ZOOK's impervious Graphite Rupture Disk Design. Applications include: food processing, dairy, breweries, pharmaceutical, distilling, baking, canning, cosmetics, biotechnology, and petrochemical industries.

Features

- Ideal for high purity and corrosion service
- Rugged design
- TFE lined to resist product buildup
- Full bore opening upon rupture
- Nominal I.D. equals the fitting size
- Self-Supporting under full vacuum at set pressures of 25 psig or higher
- Excels in liquid, gas, or two-phase applications
- 0% manufacturing range is standard
- Standard operating ratio of 90% of the marked rating on the disk tag. Higher operating ration may be available upon request. (Contact ZOOK for operating ratio on pressures below 40 psig)
- Installs using industry standard Tri-clamp®/Tri-clover® fittings (components stocked by ZOOK)
- Standard gasket material: Black Buna-N
- Sizes 1" (25mm) through 4" (100mm)
- ASME UD, CE, and TUV compliance available

Optional Features

- Burst indication (Ferrule mounted)
- Torque-rite® sanitary clamp nut (eliminates the problems associated with over/under-tightening)



SD Disk Specifications

Disk dimensions - inches (mm)			Burst Pressures psig (barg) @ 72F (22C)	
I.D. (Nominal)	O.D.	Thk.	Minimum	Maximum
1 (25)	1.984 (50.39)	0.250 (6.35)	10 (0.69)	50 (3.45)
1-1/2 (40)	1.984 (50.39)	0.250 (6.35)	7 (0.48)	50 (3.45)
2 (50)	2.516 (63.9)	0.250 (6.35)	3 (0.21)	50 (3.45)
2-1/2 (65)	3.047 (77.39)	0.250 (6.35)	2 (0.14)	50 (3.45)
3 (80)	3.579 (90.9)	0.250 (6.35)	2 (0.14)	50 (3.45)
4 (100)	4.682 (118.92)	0.250 (6.35)	1.5 (0.10)	50 (3.45)

Standard burst tolerances apply.

* Alternate sizes and disk materials, gaskets materials and lower burst ratings may be available on request – Contact ZOOK for more information

Note: max disk temperature is dependent on gasket material selected

Bulletin no. 36812 Rev. 3
 © 2009 ZOOK Enterprises, LLC, all rights reserved
 Printed in U.S.A. 3-10-2500-2500-CGG
 Tri-clamp/Tri-clover – TM Alfa Laval
 Torque-rite – TM Rubber Fab



ZOOK Enterprises, LLC
 16809 Park Circle Drive
 Chagrin Falls, OH 44022 U.S.A.
 Toll Free **800.543.1043**
 Phone **440.543.1010**
 Fax **440.543.4930**
 E-mail **sales@zook.cc**

ZOOK Canada, Inc.
 4400 South Service Road
 Burlington, ON Can. L7L 5R8
 Toll Free **800.370.6057**
 Phone **905.681.2885**
 Fax **905.681.8838**
 E-mail **sales.canada@zook.cc**

ZOOK Europe, LTD.
 Navigation House, Bridge Street
 Killamarsh, Sheffield UK. S21 1AL
 Phone **0044 (0) 1909 560999**
 Fax **0044 (0) 1909 560860**
 E-mail **zookeurope@zook.cc**

