



...provide over-pressure protection for INTERMODAL Tank Containers



Features

- Scored, forward-acting, non-fragmenting design
- Fits standard tank car safety vents or mount between ASME B16.5 Class 150 and ISO standard flanges
- Operating pressures to 85% of the disk's marked burst pressure
- Total performance tolerance $\pm 5\%$
- See table below showing disk sizes with pressure ratings and burst temperatures ready for immediate shipment
- Materials of construction
 - Disk: Nickel
 - Positioning collar, bottom ring: 316SS
 - Lining and gaskets: TFE
 - Other Materials available



Standard Ratings and Temperatures

Disk Size		Pressure Rating		Burst Temperature	
in.	mm	psig	bar	°F	°C
2.50	65	54.4	3.75	68	20
2.50	65	63.8	4.40	68	20
2.50	65	54.4	3.75	140	60
2.50	65	63.8	4.40	140	60
3.00	80	54.4	3.75	140	60
3.00	80	63.8	4.40	140	60

ICP Disk Dimensions

Disk Size		Standard Dimensions - inches (mm)					
		A		B		H	
in.	mm	in.	mm	in.	mm	in.	mm
2.50	65	3.75	95	2.50	64	0.25	6.4
3.00	80	5.00	127	2.90	74	0.38	9.7

Bulletin no. 39000 Rev. 2
© 2001, 2004 ZOOK Enterprises, LLC, all rights reserved
Printed in U.S.A. 4-15-1M-D-11.5M-CGG



ZOOK Enterprises, LLC
16809 Park Circle Drive
Chagrin Falls, OH 44022 U.S.A.
Toll Free **800.543.1043**
Phone **440.543.1010**
Fax **440.543.4930**
E-mail **sales@zook.cc**

ZOOK Canada, Inc.
4400 South Service Road
Burlington, ON Can. L7L 5R8
Toll Free **800.370.6057**
Phone **905.681.2885**
Fax **905.681.8838**
E-mail **sales.canada@zook.cc**

ZOOK Europe, LTD.
Navigation House, Bridge Street
Killamarsh, Sheffield UK. S21 1AL
Phone **0044 (0) 1909 560999**
Fax **0044 (0) 1909 560860**
E-mail **zookeurope@zook.cc**

visit us on the web at www.zook.cc