

SAMN-U

SPRING ASSISTED MULTIPLE NOSSLE DESUPERHEATER



SAMN-U has six nozzles which can be opened or closed to vary the coolant flow. This provides a higher turndown than single nozzle units where the amount of coolant flow is dependent only on the ability to vary the pressure drop across the nozzle.

SAMN-U contains an integral spring loaded flow plug which moves in response to a change in pressure differential between the coolant inlet pressure and the main header pressure. As the plug moves, more or less nozzles are uncovered introducing more or less coolant into the main header. The varying inlet coolant pressure is controlled by a separate water or coolant control valve.

The coolant enters the unit and passes through the center of the spring spacer, spring and plug. Unbalanced forces created by the coolant over line pressure differential cause the plug to move, exposing more or fewer flow nozzles. The coolant is atomized as it passes under pressure through the spray nozzles which further assist in evaporation of the coolant.

Copes-Vulcan has been providing control valves and desuperheaters for the power, process and nuclear industries since 1903. SPX provides a wide range of valves for the control of pressure, temperature and flow-induced noise in all types of power plants. Products include severe service and general service control valves, variable orifice desuperheaters, Raven™, trim and steam-conditioning valves and nuclear control valves, as well as custom designed specialty valves. Copes-Vulcan is recognized worldwide as a leader in valves for severe and critical service applications. Our strength lies in our ability to provide innovative valve solutions for our customers' application needs.

SAMN-U: Spring Assisted Multiple Nozzle Desuperheater

The spring assisted multiple nozzle desuperheater reduces steam or gas temperatures by introducing cooling liquids directly into the hot fluid.

OPERATIONAL FEATURES

- Rangeability as high as 9:1
- Temperature control to within 15°F (8°C) of saturation with the ability to hold set point within a tolerance of 10°F (6°C)
- Standard maximum available Cv of 2.50 (Ky of 2.16); higher capacity available
- Available in standard classes 150, 300, 600, 900, 1500 and 2500 per ANSI B16.5
- Cooling water pressure minimum of 225 psi (1550 kPa) to a maximum of 1000 psi (6900 kPa) above the steam header pressure at the inlet
- Mounting commonality with 'U'-Series desuperheaters

DISCHARGE NOZZLES

The multiple nozzle arrangement located near the end of the nozzle tube is typically comprised of six individual nozzles. While in a standard unit, the six nozzles are all of the same size, seven nozzle size options are available. The nozzle size selected for a given application will maximize controller and turndown.

COOLANT WATER PRESSURE

Coolant water pressure should be a minimum of 225 psi (1550 kPa) and a maximum of 1000 psi (6900 kPa) above the steam pressure during operation. Flow through the unit varies with water pressure. The plug begins to lift at approximately 60 psi (410 kPa) and reaches full travel at approximately 225 psi (1550 kPa) exposing all of the nozzles.

INSTALLATION RECOMMENDATIONS

The SAMN-U can be furnished for installation in main stream line size 6-24" (150-600mm) and larger. It is recommended that the unit be installed in a header with a minimum of five pipe diameters [not less than 4' (1.2m)] of straight pipe upstream and 16' (5m) of straight pipe downstream.

The unit can be installed in either horizontal or vertical pipe run. For vertical pipe runs, it is recommended that flow is upward and a drain pot is placed at the bottom of the pipe run. All units must be installed such that the discharge nozzles face directly downstream. The recommended location of the temperature sensing point is 25' (8m) downstream.

The mounting interface is a standard 3" (80mm) flange per ANSI B16.5 at the rated pressure class. A 2.9" (74mm) minimum diameter bore is required for insertion into the header. The SAMN-U can be attached to the header by using a standard weld-on-let and weld neck flange for pressure classes 150-900. The mounting is usually supplied by others. Special fittings for mounting are available from CopesVulcan for pressure classes 1500 and 2500 since weld reinforcement is required. Mounting gasket, studs and nuts are usually supplied by others.

DIMENSIONS

150 PRESSURE CLASS IN/(MM)				
HEADER SIZE	A	B	C	D
6" (150mm)	12.06 (306)	7.69 (195)	6.19 (157)	8.69 (221)
8" (200mm)	13.06 (332)	6.69 (170)	5.19 (132)	7.69 (195)
10" (250mm)	14.12 (359)	5.62 (143)	4.12 (105)	6.62 (168)
12" (300mm)	15.12 (384)	9.94 (253)	8.44 (214)	10.94 (278)
14" (350mm)	15.75 (400)	9.31 (237)	7.81 (198)	10.31 (262)
16" (400mm)	16.75 (425)	8.31 (211)	6.81 (173)	9.31 (237)
18" (450mm)	17.75 (451)	7.31 (186)	5.81 (148)	8.31 (211)
20" (500mm)	18.75 (476)	6.31 (160)	4.81 (122)	7.31 (186)
22" (550mm)	19.75 (502)	5.31 (135)	3.81 (97)	6.31 (160)
24" (600mm)	20.75 (527)	6.31 (160)	4.81 (122)	7.31 (186)

600 PRESSURE CLASS IN/(MM)				
HEADER SIZE	A	B	C	D
6" (150mm)	12.06 (306)	8.31 (211)	5.62 (143)	8.69 (221)
8" (200mm)	13.06 (332)	7.31 (186)	4.62 (117)	7.69 (195)
10" (250mm)	14.12 (359)	6.25 (159)	3.56 (90)	6.62 (168)
12" (300mm)	15.12 (384)	10.56 (268)	7.88 (200)	10.94 (278)
14" (350mm)	15.75 (400)	9.94 (253)	7.25 (184)	10.31 (262)
16" (400mm)	16.75 (425)	8.94 (227)	6.25 (159)	9.31 (237)
18" (450mm)	17.75 (451)	7.94 (202)	5.25 (133)	8.31 (211)
20" (500mm)	18.75 (476)	6.94 (176)	4.25 (108)	7.31 (186)
22" (550mm)	19.75 (502)	7.94 (202)	5.25 (133)	6.31 (160)
24" (600mm)	20.75 (527)	6.94 (176)	4.25 (108)	7.31 (186)

1500 PRESSURE CLASS IN/(MM)				
HEADER SIZE	A	B	C	D
6" (150mm)	12.06 (306)	8.81 (224)	5 (127)	8.69 (221)
8" (200mm)	13.06 (332)	7.81 (198)	4 (102)	7.69 (195)
10" (250mm)	14.12 (359)	6.75 (171)	2.94 (75)	6.62 (168)
12" (300mm)	15.12 (384)	11.06 (281)	7.25 (184)	10.94 (278)
14" (350mm)	15.75 (400)	10.44 (265)	6.62 (168)	10.31 (262)
16" (400mm)	16.75 (425)	9.44 (240)	5.62 (143)	9.31 (237)
18" (450mm)	17.75 (451)	8.44 (214)	4.62 (117)	8.31 (211)
20" (500mm)	18.75 (476)	7.44 (189)	3.62 (92)	7.31 (186)
22" (550mm)	19.75 (502)	8.44 (214)	4.62 (117)	6.31 (160)
24" (600mm)	20.75 (527)	7.44 (189)	3.62 (92)	7.31 (186)

300 PRESSURE CLASS IN/(MM)				
HEADER SIZE	A	B	C	D
6" (150mm)	12.06 (306)	8 (203)	6 (152)	8.69 (221)
8" (200mm)	13.06 (332)	7 (178)	5 (127)	7.69 (195)
10" (250mm)	14.12 (359)	5.94 (151)	3.94 (100)	6.62 (168)
12" (300mm)	15.12 (384)	10.25 (260)	8.25 (210)	10.94 (278)
14" (350mm)	15.75 (400)	9.62 (244)	7.62 (194)	10.31 (262)
16" (400mm)	16.75 (425)	8.62 (219)	6.62 (168)	9.31 (237)
18" (450mm)	17.75 (451)	7.62 (194)	5.62 (143)	8.31 (211)
20" (500mm)	18.75 (476)	6.62 (168)	4.62 (117)	7.31 (186)
22" (550mm)	19.75 (502)	5.62 (143)	3.62 (92)	6.31 (160)
24" (600mm)	20.75 (527)	6.62 (168)	4.62 (117)	7.31 (186)

900 PRESSURE CLASS IN/(MM)				
HEADER SIZE	A	B	C	D
6" (150mm)	12.06 (306)	8.75 (222)	5.31 (135)	8.62 (219)
8" (200mm)	13.06 (332)	7.81 (198)	4.38 (111)	7.69 (195)
10" (250mm)	14.12 (359)	6.25 (171)	3.31 (84)	6.62 (168)
12" (300mm)	15.12 (384)	11.06 (281)	7.62 (194)	10.94 (278)
14" (350mm)	15.75 (400)	10.44 (265)	7 (178)	10.31 (262)
16" (400mm)	16.75 (425)	9.44 (240)	6 (152)	9.31 (237)
18" (450mm)	17.75 (451)	8.44 (214)	5 (127)	8.31 (211)
20" (500mm)	18.75 (476)	7.44 (189)	4 (102)	7.31 (186)
22" (550mm)	19.75 (502)	8.44 (214)	5 (127)	6.31 (211)
24" (600mm)	20.75 (527)	7.44 (189)	4 (102)	7.31 (186)

2500 PRESSURE CLASS IN/(MM)				
HEADER SIZE	A	B	C	D
6" (150mm)	12.06 (306)	14.75 (375)	9.56 (243)	14.25 (362)
8" (200mm)	13.06 (332)	13.75 (349)	8.56 (217)	13.25 (337)
10" (250mm)	14.12 (359)	12.69 (322)	7.5 (191)	12.19 (310)
12" (300mm)	15.12 (384)	11.69 (297)	6.5 (165)	11.19 (284)
14" (350mm)	15.75 (400)	11.06 (281)	5.88 (149)	10.56 (268)
16" (400mm)	16.75 (425)	10.06 (256)	4.88 (124)	9.56 (243)

SAMN-U

**SPRING ASSISTED MULTIPLE
NOZZLE DESUPERHEATER**



Global locations

SPX FLOW TECHNOLOGY

5620 West Road
McKean, PA 16426
United States of America
+1 814 476 5800

SPX FLOW TECHNOLOGY

Road Two, Industrial Estate
Winsford, Cheshire CW7 3QL
England
+44 1606 552041

SPX FLOW TECHNOLOGY

25 International Business Park
#03-03/12 German Centre
Singapore 609916
+65 6264 4366

SPX FLOW TECHNOLOGY

6F Treasury Building
1568 Hua Shan Road
Shanghai 200052
PR China
+86 21 2208 5888

Based in Charlotte, North Carolina, SPX Corporation (NYSE: SPW) is a global Fortune 500 multi-industry manufacturing leader. For more information, please visit www.spx.com

SPX FLOW TECHNOLOGY

5620 West Rd.
McKean, PA 16426
P: (814)476-5800
F: (814)476-5854
E: cv@spx.com

SPX reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. For more information visit www.spx.com.

The green ">" is a trademark of SPX Corporation, Inc.

ISSUED 01/2013 CV-1165-US

COPYRIGHT © 2013 SPX Corporation